

Kodak i780 Scanner



Because mission-critical workloads demand real-world speed

We eliminated the speed bumps to make the **Kodak** i780 Scanner the one to choose for mission-critical, high-volume forms processing across a broad range of applications.

Compare specs, and you'll see that the **Kodak** i780 Scanner outruns the competition with speeds up to 130 ppm. But the i780 Scanner's actual throughput advantage is much greater than raw numbers—because, unlike competing products, it delivers maximum scanning while meeting real needs under real-world conditions. You get true 130 ppm performance when scanning:

- At up to 300 dpi resolution.
- In color, grayscale or black-and-white.
- In dual stream mode (outputting up to four images per scan!).
- With *all* advanced features enabled.

Pace-setting image processing

- Take pre-sorting right out of your business process—with the automatic orientation feature, document content

is analyzed on-the-fly and your images are automatically displayed in the correct reading orientation.

- Exclusive Perfect Page imaging delivers exceptional image quality, with readability equal to or better than the original document.
- Auto color detection for threshold-based automatic color scanning.
- Electronic color dropout allows the scanner to eliminate the form color, capturing only the information you need.
- Auto cropping, so you capture only the actual document—and deskew, to automatically straighten every image.
- Five output options meet virtually any imaging requirement—black-and-white, color or grayscale, plus two dual stream options: color and black-and-white, or grayscale and black-and-white.

Extra-versatile, efficient paper handling

- Easily scan mixed batches of business documents, photos, tear sheets and graphics.

- SurePath technology delivers the paper-feeding reliability you need for uninterrupted workflow.
- Ultrasonic multi-feed detection helps prevent misfeeds by recognizing labels, stick-on notes, and stuck-together documents.
- Flexible input tray feeds a wide range of document sizes and shapes, with lockable paper-feeding guides and an included short-document exit tray for stacking smaller documents.

Desperate for performance?

No other industry-leading scanner comparable to the **Kodak** i780 Scanner equals Kodak's combination of speed, productivity-building features and robust paper handling.

Demand more—and get more—with the affordable, high-performance i780 Scanner, only from Kodak.

Kodak Service & Support

No matter where in the world you do business, all the support you need is nearby. Our global team of service experts is there for you around the clock. Choose from a variety of service plans and enjoy maximum uptime, real convenience and peace of mind.

Kodak i780 Scanner

Recommended Daily Volume	up to 130,000 pages per day
Throughput Speeds (up to 300 dpi, landscape, letter-size documents) ppm=pages per minute, ipm=images per minute	130 ppm (up to 520 ipm*) (Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.)
Scanning Technology	Dual Tricolor Plus CCD, Grayscale output bit depth is 256 levels (8-bit), Color capture bit depth is 40-bit (10 bits per red, green, blue and black channels), Color output bit depth is 24-bit
Optical Resolution	300 dpi
Illumination	Dual long-life Xenon lamps per side, mercury-free
Output Resolution	Color/Grayscale: 100/150/200/240/300 dpi, Bitonal: 200/240/300/400 dpi
Maximum Document Size	ADF: 305 mm x 863 mm (12 in. x 34 in.), With short document exit tray: 164 mm x 164 mm (6.4 in. x 6.4 in.)
Minimum Document Size	64 mm x 64 mm (2.5 in. x 2.5 in.)
Paper Thickness and Weight	With Standard feeder: 45 g/m ² (12 lb.) bond to 200 g/m ² (110 lb.) index With Ultra-Lightweight feeder accessory: 25 g/m ² (7 lb.) rice paper to 75 g/m ² (20 lb.) bond
Feeder/Elevator	500-sheet elevator-design automatic document feeder with four settings: continuous feed, 100-sheet, 250-sheet and full 500-sheet batches; Short document exit tray included
Multi-feed Detection	With ultrasonic technology; three ultrasonic sensors that can work together or independently
Connectivity	IEEE-1394 (FireWire) Interface, 6-pin connector, IEEE-1394 card and cable included
Interface Support	TWAIN and ISIS drivers (included); document capture software from Kodak
Imaging Features (in the scanner)	Perfect Page Scanning, iThresholding, automatic color detection, autocrop, aggressive crop, deskew, electronic color dropout, dual stream scanning, orthogonal rotation, automatic orientation, halftone removal, noise removal, toggle patch
On-board Compression	CCITT Group IV; JPEG or uncompressed output
File Format Outputs	JPEG (for color and grayscale images); TIFF (for bitonal images)
Warranty (US and Canada)	90 days on-site
Electrical Requirements	100-240 V, 50/60 Hz
Operating Power Consumption	200 watts maximum
Environmental Factors	Energy Star qualified scanners: Section 508 Compliant; D.O.C. Executive Order 13221 Compliant; Mercury-free Xenon lamps; Operating temperature: 15-35° C (59-95°F); Operating humidity: 15% to 76% RH
Acoustical Noise (operator position sound pressure level)	Standby mode: <42 dB(A); Operating mode: <61 dB(A)
Recommended PC Configuration	Pentium 4 2.4 GHz processor with 512 MB RAM
Supported Operating Systems	Windows 2000 SP4, Windows XP SP2, Windows Vista (32-bit)
Approvals and Product Certifications	AS/NZS CISPR 22 Class B (C-Tick Mark), CAN/CSA-C22.2 No. 60950-1-03, Canada ICES-003 Issue 3 (Class A), GB4943, GB9254 (Class A), GB 17625.1 Harmonics (CCC "S&E" Mark), EN 55022: 2006 ITE Emissions (Class B), EN 61000-3-3 Flicker, EN 55024:1998 ITE Immunity, (CE Mark), EN 60950-1 (TUV GS Mark), IEC 60950-1, CISPR 22 (Class B), VCCI (Class A), CNS 13438:2006 (Class A), (BSMI Mark), UL 60950-1, CFR 47 Part 15 Subpart B (FCC Class A), Argentina S-Mark
Consumables Available	Feeder consumables kit, extra-large feeder consumables kit, imaging guide set, printer ink cartridge and carrier, transport cleaning sheets, roller cleaning pads, printer ink blotters, Staticide wipes, calibration targets, black imaging background
Accessories/Options	Ultra-Lightweight feed module; White imaging background; Manual feeder
Dimensions	Height: 40 cm (15.7 in.), Width: 61 cm (23.9 in.), Depth: 77 cm (30.3 in.) Weight: 38.6 kg (85 lbs.)

*ipm speeds based on dual stream output of four compressed images for each document scanned-bitonal and color or bitonal and grayscale.

To learn more:
www.kodak.com/go/i780



As an **Energy Star**® Partner, Eastman Kodak Company has determined that these products meet **Energy Star**® guidelines for energy efficiency.

Printed using Kodak Technologies.

Innovation you can count on.

Eastman Kodak Company
343 State Street, Rochester, NY 14650
1-800-944-6171

Kodak Canada, Inc.
Toronto, Ontario M9R 0A1
1-800-465-6325

Kodak GmbH
Hedelfingerstr 60
70327 Stuttgart, Germany
EAMER-DI-Capture@kodak.com

Kodak (Australasia) Pty. Ltd.
Australia: 1-800-895-747
New Zealand: 0800-2 KODAK (56325)
anz-marketing@kodak.com

Kodak (China) Investment Company Limited
Beijing +8610-6561-6561 ext. 8908

Kodak (Hong Kong) Limited
13/F Cityplaza Four, 12 Taikoo Wan Road,
Taikoo Shing
+852-2856-6501

Kodak Japan Limited
Tokyo, Japan
+81-3-5577-1380
jp-di-mktg@kodak.com

Kodak Taiwan Limited
Taipei +886-2-2950-0336 ext. 753

Kodak de Mexico
Mariano Otero 408
Guadalajara, Mexico
+52-33-3678-6124
informes@kodak.com

©Kodak, 2008. Kodak is a trademark of Kodak.
Specifications are subject to change without notice.
A-5790 CAT No. 867 9169 Printed in USA 01/08

